

Elan +2 Gearing

Type 9 5 speed standard ratios

Gear	Ratio	Diff Ratio	Overall Ratio	Tyre	Tyre dia	Tyre rolling	1000	2000	3000	4000	5000	6000	7000
1	3.65	3.77	13.76	165/13	23.65	74.32	5.11	10.23	15.34	20.46	25.57	30.69	35.80
2	1.97	3.77	7.43		23.65	74.32	9.48	18.95	28.43	37.90	47.38	56.86	66.33
3	1.37	3.77	5.16		23.65	74.32	13.63	27.25	40.88	54.51	68.13	81.76	95.38
4	1	3.77	3.77		23.65	74.32	18.67	37.34	56.00	74.67	93.34	112.01	130.68
5	0.82	3.77	3.09		23.65	74.32	22.77	45.53	68.30	91.06	113.83	136.59	159.36

Elan standard 4 speed ratios

Gear	Ratio	Diff Ratio	Overall Ratio	Tyre	Tyre dia	Tyre rolling	1000	2000	3000	4000	5000	6000	7000
1	2.972	3.77	11.20	165/13	23.65	74.32	6.28	12.56	18.84	25.13	31.41	37.69	43.97
2	2.009	3.77	7.57		23.65	74.32	9.29	18.58	27.88	37.17	46.46	55.75	65.05
3	1.396	3.77	5.26		23.65	74.32	13.37	26.74	40.12	53.49	66.86	80.23	93.61
4	1	3.77	3.77		23.65	74.32	18.67	37.34	56.00	74.67	93.34	112.01	130.68

Lotus 5 speed ratios

Gear	Ratio	Diff Ratio	Overall Ratio	Tyre	Tyre dia	Tyre rolling	1000	2000	3000	4000	5000	6000	7000
1	3.2	3.77	12.06	165/13	23.65	74.32	5.83	11.67	17.50	23.33	29.17	35.00	40.84
2	2.01	3.77	7.58		23.65	74.32	9.29	18.58	27.86	37.15	46.44	55.73	65.01
3	1.37	3.77	5.16		23.65	74.32	13.63	27.25	40.88	54.51	68.13	81.76	95.38
4	1	3.77	3.77		23.65	74.32	18.67	37.34	56.00	74.67	93.34	112.01	130.68
5	0.8	3.77	3.02		23.65	74.32	23.33	46.67	70.00	93.34	116.67	140.01	163.34

Lotus 5 speed with 3.55 diff

Gear	Ratio	Diff Ratio	Overall Ratio	Tyre	Tyre dia	Tyre rolling	1000	2000	3000	4000	5000	6000	7000
1	2.972	3.555	10.57	165/13	23.65	74.32	6.66	13.32	19.98	26.64	33.31	39.97	46.63
2	2.009	3.555	7.14		23.65	74.32	9.85	19.71	29.56	39.42	49.27	59.12	68.98
3	1.396	3.555	4.96		23.65	74.32	14.18	28.36	42.54	56.72	70.91	85.09	99.27
4	1	3.555	3.56		23.65	74.32	19.80	39.59	59.39	79.19	98.98	118.78	138.58
5	0.8	3.555	2.84		23.65	74.32	24.75	49.49	74.24	98.98	123.73	148.48	173.22